



**NOTES**

1. REINFORCEMENT: A) 6x6 W2.9 X W2.9 WELDED WIRE FABRIC FOLDED IN U SHAPE. B) 2- NO.4 1/2" Ø REINFORCEMENT BARS - GRADE 60 - EACH 11'-4" LONG.
2. CONCRETE SHALL BE MIX NO. 6 (4500 PSI).
3. 2 -SC52 - 2 TON LIFTING ANCHORS.
4. ALL BARRIERS SHALL HAVE "T350" IMPRINTED ON TOP END OF BARRIER.
5. 24" WIDE X 1 7/8" HIGH DRAIN PAN.
6. 3/4" CHAMFER ALONG TOP EDGES.
7. CONNECTOR LOOP -3/4" Ø ROD ASTM 709 GRADE 36 PLAIN SHALL CONFORM TO ASTM A 153.



APPROVED:

*Frank Murphy*  
DEPUTY DIRECTOR - OPERATIONS  
*Khalil Zane*  
DIRECTOR, DEPARTMENT OF TRANSPORTATION

CITY OF BALTIMORE  
DEPARTMENT OF TRANSPORTATION  
TRAFFIC DIVISION

**PRECAST TEMPORARY 32" F SHAPE  
CONCRETE TRAFFIC BARRIER  
(PIN AND LOOP JOINT)**

ISSUED	REVISED	REVISED
8 / 2010		

STANDARD NO.  
BC 104.05

SCALE: NONE

SHEET 1 OF 2